Exterior Coach Lights, Security Lights, and Address Lights Guidelines

Exterior Coach and Security (by the garage door) provide light into the streets for the community.

Address lights are necessary so that emergency vehicles can locate homes and address quickly.

No Exterior Coach, Security or Address lights are ever to be turned off or disconnected.

1. *To maximize light reflected from a fixture, the bulb should be contained within the frame and lens area so that lenses can reflect light outward. Clean lenses help produce more light.*
   a. Coach and Security Lights only use size A-19 Bulbs
   b. No Spiral, Flood or Spot light bulbs are allowed
   c. Community Color is Daylight 5000K (see attached color spectrum)
   d. Recommended LED 60W -100W equivalent (if possible usable in wet applications)
   e. Bulb is not to extended below Light Fixture Frame
   f. Colored Bulbs are not allowed except during Holiday seasons
   g. Adding additional exterior lights or changing lights requires ARC approval
   h. Community address light color is Warm White (see attached for manufacturer – Aero-Lite - information for both bulbs and covers)

Cameras, TV Dishes, Motion Detector Lights, Solar Panels Guidelines

2. *All of the above items require ARC approval before installation*
   a. All vertical cords and cables must be painted the house color
   b. No horizontal cords or cables are to be seen hanging from or along the house or walls.
   c. No extension cords are to be used to connect to the light fixture, nor are electrical receptacles to be used for power. All fixtures are to be permanently wired and meet electrical code.
   d. Motion Detector lights are to be angled downward to avoid high light levels for drivers



Recommended style, color and Wattage-60W to100W equivalent, size is A19. Brand is optional.

Contact Aero-Lite manufacturer for address cover replacements and address lightbulbs.